

Multiple-Stream-Blender







MSB

The Centec blending system optimises beverage production by maximising the existing production capacity and precisely adjusting the "Brix/Diet content. The system allows the direct blending of Water and Syrup/Concentrate in an one-step process and to adjust the "Brix/Diet value very precisely. Highly accurate flow meters and pneumatic control valves continuously monitor and adjust the mass ratio. A redundant Centec on-line density sensor, placed at the end of the system, accurately determines the "Brix/Diet content of the final product and if necessary, the mass ratio is automatically adjusted. An optional remote access service kit allows a Centec technician, located in Frankfurt, to update and maintain system software at any time. If required, the system can be equipped with a deaeration and carbonation system.

Technical Data

Capacity	10-150.00 l/h
Diameter	DN20 – DN150
Range of Dosing	0-65°Brix ± 0,025
Temperature	2°C – 85°C
Cleaning	CIP-up to 85°C
Material	1.4301 / 1.4404 / AISI
Gasket / Sealing	EPDM
Optional	Water Deaeration System Oxygen Measurement Pre-Carbonation Chiller / Flash Pasteuriser Remote Access Kit

UK representative and distributor: Protecnica Solutions Limited. Stalworths, The Street, Great Tey, Colchester, Essex, CO6 1JS, United Kingdom

www.centec-systems.co.uk info@centec-systems.co.uk

Centec GmbH
Wilhelm-Röntgen-Str. 10 • 63477 Maintal/Frankfurt
Tel.: +49 (0)6181 1878 0 • Fax: +49 (0)6181 1878 50 info@centec.de • www.centec.de



